

Cyclone[®]

Better farms start with Cyclone

GATES



- APPLICATION • FEATURES AND BENEFITS • SPECIFICATIONS
- GATE FITTING HINGE KITS

onesteel

www.onesteelcyclone.com.au

Cyclone® Gates

APPLICATION

Cyclone manufactures a wide range of quality rural gates. All Cyclone gates are manufactured in Australia, and made from pre-galvanised pipe and mesh.

Cyclone rural gates are available in a variety of lengths and styles to suit a wide range of fencing applications and gateways, and are all manufactured to a height of 1170mm.

All the pipe bracing and bottom bars are shear cut to increase the surface contact at the weld, combined with a pre-designed weld pattern specified to be a minimum of 25mm, deliver both improved strength and consistency. All welds are then painted with a rust inhibitive coating.

In the vertical and N brace gates, the mesh is welded flush with the inside edge of the frame, to reduce the chance of injury to both you and your livestock.

“A good gate completes a great fence”

N Brace Gate

The Cyclone N-brace gate is a strong ‘multi purpose’ rural gate and is available in both left and right side hand configurations. Be sure to check with your distributor when ordering.

The ‘N’ shaped internal brace is welded to the main frame, and is designed to achieve maximum strength to suit a broad range of applications. The combination of the ‘N’ brace design and the addition of the welded mesh make the ‘N’ brace gate the strongest gate in the Cyclone range, with the added benefit of providing an excellent barrier to both livestock and feral pests.

Cyclone ‘N’ brace gates are made from 25nb galvanised pipe, with a wall thickness of 2mm, and a 5mm mesh thickness.

Vertical Brace Gate

The Cyclone vertical brace gate is a versatile ‘value for money’ rural gate that can be hinged from either the left or right side, depending on the user’s requirements.

The vertical brace and mesh insert is welded to the gate frame to increase rigidity and the overall strength, with the additional benefit of the mesh not only increasing the strength of the gate but also providing an excellent barrier to both livestock and feral pests.




They are made from 25nb galvanised pipe, with a wall thickness of 2mm, and a 5mm pre-galvanised mesh.

5 Bar Gate

The Cyclone ‘5’ bar gate is ideal for use as a farm entry gate, and is perfectly suited for use in cattle holding yards & livestock situations.

The ‘5’ bar gate is designed to improve the overall strength of the gate, with the focus on lateral pressure often experienced with larger livestock, and is an excellent economical option for low intensity holding yards for cattle.

Cyclone ‘5’ bar gates are made from a 25nb galvanised pipe frame, with 20nb cross bars, of a wall thickness of 2mm, and a single vertical steel strap.

		GATES & FEATURES	BENEFITS		OPENING WIDTH	GATE WIDTH (MM)	VERTICAL BRACES*	
Heavy Duty	N Brace Gate	<ul style="list-style-type: none"> - Gal 25nb frame - Gal 20nb brace - ‘N’ shaped brace - Mesh insert 	<ul style="list-style-type: none"> - Good corrosion resistance - Additional frame strength - 100mm x 250mm x 5mm 		10’ 12’ 14’ 16’	3.00m 3.60m 4.20m 4.80m	2970 3570 4170 4770	- - - -
	Vertical Brace Gate	<ul style="list-style-type: none"> - Gal 25nb frame - Gal 25nb brace - Vertical braces - Mesh insert 	<ul style="list-style-type: none"> - Good corrosion resistance - Additional frame strength - 100mm x 250mm x 5mm 		3.3’ 8’ 10’ 12’ 14’ 16’	1.00m 2.40m 3.00m 3.60m 4.20m 4.80m	2370 2970 3570 4170 4770	- 1 1 1 2 3
	5 Bar Gate	<ul style="list-style-type: none"> - Gal 25nb frame - 20nb diameter horizontal bars - Vertical flat bar 32x5mm 	<ul style="list-style-type: none"> - Good corrosion resistance - Ideal for cattle yards - Additional frame strength 		8’ 10’ 12’ 14’	2.40m 3.00m 3.60m 4.20m	2370 2970 3570 4170	1 1 2 2
	SupaGal®							

* Number of vertical support braces

GATE FITTING HINGE KITS

Cyclone stocks a wide range of gate fitting hinge kits, suitable for steel, timber, and concrete strainer posts. FGP style gate fitting hinge packs are designed for strength and durability and are hot dipped galvanized for superior corrosion resistance. The long pin gudgeons utilise a unique UV stabilised self-lubricating poly bush, which eliminates metal to metal contact for an extremely smooth long life gate operation. The design of the latches makes it virtually impossible for horses & cattle to manipulate, while they are easily opened from horseback or motorcycle.

Cyclone also stocks Franklin gate packs, which are available with an electro-galvanized coating for protection in less corrosive environments.

LIGHT DUTY GATE PACK FGP2

Hot dipped galvanized
For timber strainer posts

Screw in bottom gudgeon
and screw in hinge strap



CYCLONE STEEL STRAINER GATE PACK FGP7

Hot dipped galvanized
For Cyclone steel strainer posts

Bolt on gudgeon and hinge strap for angle post



STANDARD DUTY GATE PACK FGP1

Hot dipped galvanized
For timber strainer posts
Adjustable - top only

Screw in bottom gudgeon
and bolt through hinge strap



Bolt length*: 350mm

BROOKER GATE PACK FGP20

Hot dipped galvanized
For timber strainer posts
Adjustable - top & bottom



Bolt length*: 410mm

HEAVY DUTY GATE PACK FGP4

Hot dipped galvanized
For timber strainer posts
Adjustable - top & bottom

Bolt through bottom gudgeon
and bolt through hinge strap

Bolt length & gudgeon*: 350mm



FRANKLIN TIMBER GATE PACK*

Electro-galvanized
For timber strainer posts
Adjustable - top & bottom



Bolt length & gudgeon*: 400mm

HEAVY DUTY DOUBLE GATE PACK FGP8

Hot dipped galvanized
For timber strainer posts
Adjustable - top & bottom

Bolt through bottom gudgeon
and bolt through double gate hinge straps

Bolt length & gudgeon*: 350mm



FRANKLIN CONCRETE GATE PACK

Electro-galvanized
For concrete strainer posts
Adjustable - top & bottom



Bolt length: 400mm
Gudgeon: 350mm

* Suitable for approx 300mm timber posts

Visit www.onesteelcyclone.com.au or call Cyclone Sales & Service on 1800 199 450